

"STRONG" SHELVING

## **FOR HIGH LOADS**

			In tor heavy duties, is particularly solid and ige standard module can be 200 cm long and 90 cm.			
$\left( \begin{array}{c} ( ) \\ ( $	Max. load capacity certified according to Eurocode 9. Up to 700 kg per each shelf	-30°	Tested in cold rooms (down to - 30° C)			
AL+PP +AISI 304	Anodized aluminium alloy structure + copolymer polypropylene staves + AISI 304 stainless steel cover		Adjustable feet			
	Long-lasting stability, no rust, 10-year warranty against water and moisture corrosion		Easy and quick assembly: snap-fit, no special tool needed			
EN AW-6060	Suitable for direct food contact, in compliance with European Community requirements	НАССР	Easy to clean and sanitize in accordance with HACCP			
<b>1</b>	Designed according to European security requirements		Removable staves, washable in dishwasher			
and the	Stable and resistant: no anchor plates, stabilizer bars or cross joints, no plastic connections		High variety of depths. Standard: 30, 40, 45, 60, 70, 75, 80, 85, 90 cm			
\$	Open-faced corner compositions for storage optimization	lilili	Made to measure. Lengths every 32 mm (Q and Q-I shelves) and every 90 mm (P shelf)			

## AVAILABLE MEASURES AND TECHNICAL SPECIFICATIONS:

- Height:

CAP



measures available upon request; standard:150, 180, 200 cm Requested number of levels, adjustable height every 15 cm 30, 40, 45, 60, 70, 75, 80, 85, 90 cm (other width upon request) "P" shelves: available every 9 cm

"Q" shelves: available every 3,2 cm "P-I / Q-I" shelves: available every 5 cm

R kg	"P/P-I"							
Re ke			DEPTH		"Q/Q-I"		DEPTH	
ke		cm	30-45	60-90		cm	30	40-90
	LENGTH	100	725 kg	695 kg	LENGTH	100	660 kg	440 kg
PIN AND CLIP SYSTEM		127	510 kg	435 kg		125	500 kg	500 kg
		154	350 kg	295 kg		152	320 kg	320 kg
o– UPRIGHT	Hooked shelves (corner-shaped shelving):Hooked shelves (corner-shaped shelving):from 150 to 500 kg each, according to the compositionfrom 150 to 280 kg each, according to the composition							
CAP FOR UNUSED UPRIGHT HOLES		P	stave single Th	th stave is 50 to is 40 mm). T stave model, s (yo e picture belo	If with polypro mm and the s Fhe picture abo suitable for 30 bu can see how sta w shows the c 70, 75, 80, 85 a	pace betwee ove shows th , 40 and 45 ( aves can be rem louble stave	en ne cm oved)	
ADJUSTABLE FEET	perforate assemble	with polyprop ed staves, ed side by sic how staves can	de		Q		E	1
		_	P	-I/Q-I	P-I and Q-I		inless steel co be combined ctively	
	134P/Q			3	Ava		or salami with vith 3 bars or 136P/C	4 bars
PAIRS OF HOOKS (FOR CORNER COMPOSITIONS)					<b>A.I.</b> G Via L 3017 T: +3	a.i. attrezzatu iuidovie s.r. azzarini 14/	. guidovie re per il punto vena I. 16, RA - (VE) Italy 21	lita